Applicant: Craig A. Schmitt Attorney's Docket No.: 00635-234001

Serial No.: 10/771,621 Filed: February 4, 2004

Page : 2 of 9

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## Listing of Claims:

- 1. (Withdrawn) A one-piece manifold for a reverse osmosis system, comprising:
  - a filter configured to receive water from a water port;
- a membrane configured to receive filtered water via a first conduit, the membrane configured to send permeate water to a reverse osmosis tank; and
- a flow restrictor configured to receive concentrate water from the membrane via a second conduit and to pass the concentrate water to a drain port.
- 2. (Withdrawn) The manifold of claim 1, further comprising: a shut-off valve.
- 3. (Withdrawn) The manifold of claim 1 wherein the manifold comprises polypropylene material.
- 4. (Withdrawn) The manifold of claim 1, wherein the filter is a sediment filter.
- 5. (Withdrawn) The manifold of claim 4, further comprising:
  a carbon filter
- 6. (Withdrawn) The manifold of claim 5, further comprising:
  end caps including grooves that control the path of water flow to the filters.

Applicant: Craig A. Schmitt Attorney's Docket No.: 00635-234001

Serial No.: 10/771,621 Filed: February 4, 2004

Page

7. (Withdrawn) The manifold of claim 6, wherein the end caps control the path of water flow from each of the filters and the membrane.

8. (Withdrawn) The manifold of claim 1, wherein the flow restrictor includes threads that restrict the flow of water.

9. (Withdrawn) A one-piece manifold for a zero-waste reverse osmosis system, comprising:

a filter configured to receive water from a water port;

a membrane configured to receive filtered water via a first conduit, the membrane configured to send permeate water to a reverse osmosis tank; and

a flow restrictor configured to receive concentrate water from the membrane via a second conduit and to pass the concentrate water to a water source port.

10. (Withdrawn) The manifold of claim 9, further comprising: a shut-off valve modified for zero-waste.

11. (Withdrawn) The manifold of claim 9 wherein the manifold comprises polypropylene material.

12. (Withdrawn) The manifold of claim 9, wherein the filter is a sediment filter.

13. (Withdrawn) The manifold of claim 12, further comprising: a carbon filter

14. (Withdrawn) The manifold of claim 13, further comprising: end caps including grooves that control the path of water flow to the filters. Applicant: Craig A. Schmitt Attorney's Docket No.: 00635-234001

Serial No.: 10/771,621 Filed : February 4, 2004

Filed: February 4, 2004

Page : 4 of 9

15. (Withdrawn) The manifold of claim 14, wherein the end caps control the path of water flow

from each of the filters and the membrane.

16. (Withdrawn) The manifold of claim 9, wherein the flow restrictor includes threads that

restrict the flow of water.

17. (Original) A flow restrictor defining a restricted flow path for liquid, said flow restrictor

comprising:

a housing defining an elongated conduit having a tapering conical wall defining a first

screw thread and a water-channel thread extending therealong including generally between a first

opening into a distal region of the conduit for receiving a flow of liquid and a second opening

into a proximal region of the conduit, and

an axially elongated plug received into said conduit, a surface of said plug opposed to

said tapering conical wall defining a second screw thread and a tapering surface, said second

screw thread disposed in threaded engagement with said first screw thread defined by said

conical wall of said housing, opposed surface of said water-channel thread and said tapering

surface of said plug being disposed in sealing engagement within said conduit and opposite to

define a region for liquid flow, said housing with said water-channel thread and said tapering

surface of said plug thereby cooperatively defining a generally spiral liquid flow path along said

water-channel screw thread and said tapering surface, for flow of liquid generally between said

first opening and said second opening for delivery of liquid from the conduit.

18. (Original) The flow restrictor of claim 17, wherein said plug is received into said conduit

through said second opening.

19. (Original) The flow restrictor of claim 17, wherein said plug and said housing are injection

molded.

Applicant: Craig A. Schmitt Attorney's Docket No.: 00635-234001

Serial No.: 10/771,621 Filed : February 4, 2004

: 5 of 9 Page

20. (Currently amended) The flow-restrictor of claim 19, wherein said plug comprises a first material, said an insert comprises a second material, said first material being softer than said second material.

- 21. (Original) The flow restrictor of claim 17, wherein the first screw-thread comprises a pointed protrusion.
- 22. (Original) The flow restrictor of claim 21, wherein being disposed in sealing engagement comprises the pointed protrusion penetrating the surface of the tapered surface.
- 23. (Original) The flow restrictor of claim 17, wherein the plug comprises a third screw thread, the second screw thread and the third screw thread are separated by a gap.
- 24. (Original) A flow restrictor defining a restricted flow path for liquid, said flow restrictor comprising:

a housing defining an elongated conduit having a tapering conical wall defining a first screw thread and a water-channel thread extending therealong including generally between a first opening into a distal region of the conduit for receiving a flow of liquid and a second opening into a proximal region of the conduit, and

an axially elongated plug received into said conduit, a surface of said plug opposed to said tapering conical wall defining a second screw thread and a tapering surface, said second screw thread disposed in threaded engagement with said first screw thread defined by said conical wall of said housing, opposed surface of said water-channel thread and said tapering surface of said plug being disposed in sealing engagement within said conduit and opposite to define a region for liquid flow, said housing with said water-channel thread and said tapering surface of said plug thereby cooperatively defining a generally spiral liquid flow path along said water-channel screw thread and said tapering surface, for flow of liquid generally between said first opening and a port defined by said flow restrictor for delivery of liquid from said conduit.

Applicant: Craig A. Schmitt Attorney's Docket No.: 00635-234001

Serial No.: 10/771,621

Filed : February 4, 2004 Page : 6 of 9

25. (Currently amended) The flow restrictor of claim 24 17, wherein said plug, at least in part, defines an aperture interconnecting said conduit and said port.

26. (Currently amended) The flow restrictor of claim 25 19, wherein said port is defined, at least in part, by said plug.